


AE20 - VM2 Vehicle Mount





























Cannon Type

• Calibre:

• Rate of fire:

• Muzzle velocity:

• Range (max):

• Range (effective)

• Recoil force (max):

• Recoil force (mean):

• Weight of cannon (less magazine):

• Weight of belt feed Drum magazine:

20 x 110 mm

620 - 780 rpm

835 m/s (2,740 ft/s)

5,700 m (6,234 yds)

2,000 m (2,187 yds)

4.5 kN (1,012 lbf)

1.6 kN (360 lbf)

42.8 kgf (94.4 lbf)

5.6 kgf (12.3 lbf)

## AMMUNITION

TP & TP-T

HE & HE-T

HEI & HEI-T

AP & AP-T

API & API-T

Target practice (+ Tracer)

High explosive (+ Tracer)

High explosive incendiary (+ Tracer)

Armour piercing (+ Tracer)

Armour piercing incendiary (+ Tracer)







THE MOUNT

Traverse arc: 360° with optional adjustable safety arc stops

Elevation arc: -10° to +50°

Swept radius: 1.68 m (66 in) at 0° elevation

• Height: 1 m (39.5 in) centre line from

mounting base

Weight (Less gun & ammunition): 75 kgf (165 lbf)

**DESCRIPTION** 

Email: sales@aei-systems.com

The AE20-VM2 is a lightweight all Aluminium vehicle weapon mount for the 20 mm HS804 gun. The mount accepts AEI's drum type belt feed mechanism and flexi-chute for prolonged target engagements. The mount also accepts AEI's lower profile 'flat' belt feed mechanism and can simply revert to accept AEI's linkless feed drum magazine associated with the AE20-NM naval mount.

The cradle is spring loaded to assist the operator engage elevated targets and balance the gun horizontally whilst vehicle trundling.

The weapon mount can be readily fitted to the vehicle slewing ring, roof, bulkhead or pedestal.

The ammunition feed tank can be mounted to suit individual vehicle installations and linked to the mount with AEI's flex-chute.





## AEI Systems Ltd

1 Kings Ride Park, Ascot, Berkshire. SL5 8AP United Kingdom

